



Technical Data Sheet Antiquing Solution

DESCRIPTION

Metal Veneers is a specially formulated real metal paint range, guaranteed to be easy to use for even the most discombobulated novice paint user. Our carefully guarded recipe combines real metal elements to provide the very best pure metal finish for patrons with even the most exacting of tastes. Our Antiquing Solution allows you to age your new metal surface in mere moments – transforming from sleek to aged chic in the blink of an eye.

SUITABILITY

Suitable to be used in conjunction with Metal Veneers Copper and Robbers or Iron Horse paint effects.

COVERAGE

7 square feet or 0.7 square metres

PREPARATION

- The area should be well ventilated and have enough room for you to work comfortably.
- Make sure the surface you want to spray is clean, dust free and dry.

APPLICATION

And now the clever bit: creating a natural looking patina on your metal surface by applying our Metal Veneer Antiquing Solution.

1. Add 238ml of water to the Metal Veneers Antiquing Solution trigger sprayer bottle.
2. Replace the sprayer lid and screw on tightly to avoid any annoying spillages.
3. Give the bottle a really good shake to make sure the Antiquing Solution is mixed thoroughly.
4. Leave for 5 minutes.
5. Rub the fully dried surface of your project with a scotch pad or wire wool to produce a raw metal surface and ensure an even aged effect.
6. Spray the Antiquing Solution on all the areas you wish to age.

7. The Antiquing Solution will tend to bead on the surface, if you wish to produce an even aged surface, rub the solution in with a scotch pad or wire wool.
8. Allow to dry and develop for 1 hour before adding any further layers of Antiquing Solution, which will create a deeper aged patina.
9. When you have achieved your chosen level of patina, rinse the object with water, to neutralise the surface and slow down the ageing process.

FINISHING

To seal in the dust created by the aged surface, why not use Metal Veneers Signed, Sealed, Delivered 1K Dust Sealer.

Alternatively, leave your project unsealed to allow the surface to weather naturally with time.

HEALTH AND SAFETY

IMPORTANT:

Read the safety warnings on the back of the product and the MSDS before use.

Due to the inability of our company to anticipate or control conditions whereby our products will be employed, we do not represent or guarantee that any of our products are fit for a particular purpose. Our products should be tested by users to determine suitability for a particular purpose. We disclaim responsibility for claims and damages beyond replacement of any defective product. There are no warranties which extend beyond the description on the face here of.